Quintrex Busta – 30hp

Hawkesbury Afloat at BROOKLYN MARINA

Ph: 9985 7722

4 person Fast Tinnie

STAFF - checklist before starting:

- 1. Ensure "Hirer" is in correct boat
- 2. Explain only skipper can drive the boat
- 3. WHITE Safety Box/Floatation Device
- 4. Ensure fuel hose is connected
- 5. Check fuel, cap is firmly closed on tank and breather is open & tank's laying flat
- 6. Squeeze fuel bulb pump until firm.
- 7. Ensure fuel line is not pinched.
- 8. Check life jacket numbers
- 9. Check RED cord
- 10. Check anchor & rope
- 11. Check fire extinguisher

Motor Components Diagram

- 1. Cowling Cover
- 2. Fuel hose connection
- 3. Gear and throttle cables
- 4. Hydraulic steering unit


White Safety Box / Floatation Box is at helm

- How to tilt motor up (at helm): 1. Ensure engine is off
- 2. Ensure there are no persons in water.
- 3. Push the black tilt button on throttle lever and motor will lift up



How to tilt motor up (at motor):

- 4. Ensure engine is off
- 5. Ensure there are no persons in water, especially at rear of boat
- 6. Push the black tilt button on port side of motor (up on rocker switch)



How to tilt motor down (on motor or helm):

- 1. Ensure engine is off
- 2. Ensure there are no persons in water
- 3. Push the black tilt button on throttle lever or port side of motor and motor will slowly tilt down.

SAFETY EQUIPMENT in WHITE FLOATATION BOX

- 4 x life jackets & 1 x paddle
- 1 x first aid kit (in box)
- 1 x bailing container
- 1 x torch (in box)
- Fire extinguisher (in box)
- Emergency stop cord
- Air horn & flare (in box)

How to (drop) anchor:

- 1. Do not anchor under bridges or over sea grass beds or over submerged cables
- 2. Ensure rope is untangled then drop anchor overboard at bow
- 3. Wait for tension on rope, allow an extra metre or so of slack
- 4. Then tie off on the bow of boat

How to lift anchor:

- 1. Have motor running & not in gear
- 2. Untie rope at bow and pull in rope
- 3. If you cannot pull in anchor because it is stuck you may have to cut the line and lose anchor and bond. OR - try and drive over anchor and this may dislodge the anchor from bottom. But you may risk getting anchor line caught in propeller and lose bond.

Steering:


- 1. To steer left move steering wheel left
- 2. To steer right move steering wheel right
- 3. Speed is controlled by throttle arm

Tips:

- 1. Do not reverse motors to slow down/stop
- 2. When docking and departing ensure all are seated
- 3. Read do's and don'ts on our Map
- 4. Avoid fishing fines (have a fishing licence) & don't keep undersized fish
- 5. If a big boat leaves large waves steer front-on into the waves slowly
- 6. DO NOT drive boat onto beaches
- 7. Motors will not start if throttle levers aren't in neutral
- 8. For turning turn wheel THEN put into gear
- 9. Ensure you have your mobile phone with you and it's charged - this number is on our contract.

How to start motor:

1. Place gear shift in neutral. You know it is neutral position when you can hear a click and red button clicks



Ensure no person is in water near motor

- 2. Turn key quickly clockwise like a car
- 3. Push red button on throttle arm up and push throttle forward to engage forward gear

How to stop motor:

- 1. Place gear shift to neutral position
- 2. Turn key off (anticlockwise)

Emergency motor stop:

1. Pull red cord from base

OIL

• The motor is 4 stroke and oil is not premixed. Staff will keep this topped up.

Inventory Checklist

- 1 x 30hp outboard
- 1 x fuel tank and line
- 4 x life jackets (in front of boat)
- 1 x paddle (in boat)
- 1 x anchor & line
- 1 x alu bimini frame with cover
- 1 x bilge pump
- 1 x bailing container (in boat)
- 1 x steering wheel
- 1 x hydraulic steering unit & hoses
- 1 x battery & battery box
- 1 x fire extinguisher (in white safety kit)
- 1 x First Aide Kit (in white safety kit)